10/100/1000 Ethernet TAP



Easy 24 x 7 access to your Gigabit Ethernet segments.

Ideal for security applications and anywhere you need non-intrusive, dedicated access to your network links

The 10/100/1000 Ethernet TAP from Datacom Systems provides easy 24x7 access to your Gigabit Ethernet segments.

A convenient DIP switch on the back of the tap can be used to select auto-negotiation at 10/100 or fixed speed and duplexing settings at 1000Mbps. The 10/100/1000 Ethernet Tap's fault tolerant design will help ensure that network performance and integrity will not be affected by power loss.

- Permanent In-Line access to 10/100/1000 Ethernet links- eliminates the need for network connectors to be disconnected and connected each time a segment needs to be analyzed or monitored
- Redundant power supply insures seamless monitoring even if the main power source is unavailable
- Ideal for Security and Monitoring applications
- View ALL seven layers of network traffic
- View ALL traffic on both sides of full duplex links
- Comes with convenient built-in rack-mount or use an optional rack-mount package to mount 3 units (at 1U) and up to 14 units (at 4U).

Technical Specifications

NETWORK PORTS

One (1) 10/100 or 1000MB (RJ45) Network Connection
One (1) 10/100 or 1000MB (RJ45) Tap/Monitoring Connection

POWER REQUIREMENTS

Two (2) External AC Adapters (included) Input: 100-240 VAC, 50-60Hz, 0.8A

PHYSICAL DIMENSIONS (H x W x D)

1.07 x 5 x 5 in. (2.7 x 12.7 x 12.7 cm)

WEIGHT

12 oz. (0.34 Kgs)

CERTIFICATIONS

CE, ROHS

ENVIRONMENTAL

Operating Temperature: 32° to 104°F (0° to 40°C) Storage Temperature: -22° to 149°F (-30° to 65°C) Humidity: 5 to 90% non-condensing

WARRANTY

2-year limited warranty

ORDERING INFORMATION

Product

10/100/1000-TAP RMC-3 RMC-12-3

Description

10/100/1000 Ethernet Tap 3-Unit Rack Mount (shown below) 12-Unit Rack Mount

Find out more. Visit www.datacomsystems.com





ComWorth Solutions Pte Ltd Tel: +65 6748 2260 Fax: +65 67482267

Email: info@comworth.com.sg
Website: http://www.comworth.com.sg

